

OBJECT ORIENTED PROGRAMMING WITH JAVA

Input-Output Handling in Java – I

Debasis Samanta

Department of Computer Science & Engineering
Indian Institute of Technology Kharagpur



Input-Output Streams in Java




Stream in Java

Java treats flow of data as **stream**.


Java streams are classified into two basic types, namely, **input stream** and **output stream**.

The **java.io** package contains a large number of stream classes to support the **streams**.






Input and output streams



(a) Reading data into a program



(b) Writing data to a destination



Java Classes for I-O Streams



I-O stream classes in Java

Java provides `java.io` package which contains a large number of stream classes to process all types of data

➤ Byte stream classes


- Support for handling I/O operations on bytes

➤ Character stream classes

- Supports for handling I/O operations on characters



Taxonomy: Java stream classes






Java Input Stream Classes




Taxonomy: Java stream classes





Java input streams classes





Java input stream classes

InputStream classes is used to read 8-bit bytes and supports a number of input-related methods

- Reading bytes
- Closing streams
- Marking positions in streams
- Skipping ahead in streams
- Finding the number of bytes in stream
- and many more...



Some input stream methods

Method	Description
<code>read()</code>	Read a byte from the input stream
<code>read(byte b[])</code>	Read an array of bytes into b
<code>read(byte b[], int n, int m)</code>	Reads m bytes into b starting from n th byte
<code>available()</code>	Gives number of bytes available in the input
<code>skip(n)</code>	Skips over n bytes from the input stream
<code>reset()</code>	Goes back to the beginning of the stream
<code>close()</code>	Close the input steam

Example:

DataInputStream

<code>readShort()</code>	<code>readDouble()</code>
<code>readInt()</code>	<code>readLine()</code>
<code>readLong()</code>	<code>readChar()</code>
<code>readFloat()</code>	<code>readBoolean()</code>
<code>readUTF()</code>	



Example: Use of class `InputStream`


- Reading bytes
 - `int read()`
 - `int read (byte b[])`
 - `int read (byte b[], int off, int len)`
 - Closing streams
 - `void close()`
 - Finding the number of bytes in a stream
 - `int available()`
- Skipping ahead in a stream
 - `long skip (long n)`
 - Marking positions in a stream
 - `void mark (int limit)`
 - `void reset()`
 - `boolean markSupported()`



Java Output Stream Classes



Taxonomy: Java stream classes






Java output stream classes

OutputStream classes is used to write 8-bit bytes and supports a number of input-related methods

- Writing bytes
- Closing streams
- Flushing streams
- etc.



Java output stream classes





Some methods in output stream classes

Method	Description
write ()	Write a byte from the input stream
write (byte b[])	Write all bytes in the array b to the output steam
write (byte b[], int n, int m)	Write m bytes from array b starting from n th byte
close()	Close the output stream
flush()	Flushes the output stream

Example:

DataOutputStream

writeShort()	writeDouble()
writeInt()	writeLine()
writeLong()	writeChar()
writeFloat()	WriteBoolean()
writeUTF()	



Use of class `OutputStream`

Writing bytes

- `void write (byte b)`
- `void write (byte b[])`
- `void write (byte b[], int off, int len)`

Closing a stream

- `void close()`

Clearing a buffer


- `void flush()`



Character Stream Classes



Taxonomy: Java stream classes





Character stream classes

Character stream classes is used to read and write characters and supports a number of input-output related methods

➤ Reader stream classes


- To read characters from files.
- In many way, identical to [InputStream](#) classes.

➤ Writer stream classes


- To write characters into files.
- In many way, identical to [OutputStream](#) classes.



Reader stream classes



Writer stream classes





List of Important tasks and their Classes

Task	Character Stream Class	Byte Stream Class
Performing input operations	Reader	InputStream
Buffering input	BufferedReader	BufferedInputStream
Keeping track of line numbers	LineNumberReader	LineNumberInputStream
Reading from an array	CharArrayReader	ByteArrayInputStream
Translating byte stream into a character stream	InputStreamReader	(none)
Reading from files	FileReader	FileInputStream
Filtering the input	FilterReader	FilterInputStream
Pushing back characters/bytes	PushbackReader	PushbackInputStream
Reading from a pipe	PipedReader	PipedInputStream
Reading from a string	StringReader	StringBufferInputStream
Reading primitive types	(none)	DataInputStream
Performing output operations	Writer	OutputStream
Buffering output	BufferedWriter	BufferedOutputStream
Writing to an array	CharArrayWriter	ByteArrayOutputStream
Filtering the output	FilterWriter	FilterOutputStream
Translating character stream into a byte stream	OutputStreamWriter	(none)
Writing to a file	FileWriter	FileOutputStream
Printing values and objects	PrintWriter	PrintStream
Writing to a pipe	PipedWriter	PipedOutputStream
Writing to a string	StringWriter	(none)
Writing primitive types	(none)	DataOutputStream

Thank You

OBJECT ORIENTED PROGRAMMING WITH JAVA

Input-Output Handling in Java – II

Debasis Samanta

Department of Computer Science & Engineering
Indian Institute of Technology Kharagpur



Usage of I-O Stream Classes



Get input using DataInputStream class

Calculator Program

```
import java.io.*;
class InterestCalculator
{
    public static void main(String args[ ] )
    {
        Float principalAmount = new Float(0);
        Float rateOfInterest = new Float(0);
        int numberOfYears = 0;

        DataInputStream in = new
        DataInputStream(System.in);
        String tempString;
        System.out.print("Enter Principal
        Amount: ");
        System.out.flush();
        tempString = in.readLine();
        principalAmount =
        Float.valueOf(tempString);
        System.out.print("Enter Rate of
        Interest: ");
```

```
        System.out.flush();
        tempString = in.readLine();
        rateOfInterest =
        Float.valueOf(tempString);
        System.out.print("Enter Number of Years:");
        System.out.flush();
        tempString = in.readLine();
        numberOfYears =
        Integer.parseInt(tempString);
        // Input is over: calculate the interest
        int interestTotal =
        principalAmount*rateOfInterest*numberOfYears;
        System.out.println("Total Interest = " +
        interestTotal);
    }
}
```



Files Handling in Java



Java File I/O

Java provides `java.io` package which includes numerous class definitions and methods to manipulate file and flow of data (called File I/O streams)

There are
four major
classes:

File

FileInputStream

FileOutputStream

RandomAccessFile



Using class **File**



Opening a File object

- There are three constructors
 - Way 1:
 - `File myFile;`
 - `myFile = new File(fileName);` // Constructor 1
 - Way 2:
 - `File myFile;`
 - `myFile = new File (pathName, filename);` // Constructor 2
 - Way 3:
 - `File myFile;`
 - `File myFile = new File(myDir, fileName);` // Constructor 3



Using class `File`



Dealing with file names

- `String getName()`
- `String getPath()`
- `String getAbsolutePath()`
- `String getParent()`
- `boolean renameTo(File newFilename)`



Using class **File**



Testing a file

- `boolean exists()`
- `boolean canWrite()`
- `boolean canRead()`
- `boolean isFile()`
- `boolean isDirectory()`
- `boolean isAbsolute()`



Using class **File**



Getting file information

- `long lastModified()`
- `long length()`
- `boolean delete()`

Directory utilities

- `boolean mkdir(File newDir)`
- `boolean mkdirs(File newDir)`
- `String [] list()`



Checking Status of a File



Using class **File**: An example

```
import java.io.File  
class FileTest {  
    public static void main (String args [ ] ) throws IOException {  
        File fileToCheck;  
        ...  
    }  
}
```

```
public static void getPaths (File f ) throws IOException {  
    ...  
}
```

```
import java.io.File  
class FileTest {  
    public static void main (String args [ ] ) throws IOException {  
        File fileToCheck;  
        if (args.length > 0 ) {  
            for (int i = 0; i < args.length;i++ ) {  
                fileToCheck = new File(args[ i ] );  
                getPaths(fileToCheck);  
                getInfo(fileToCheck);  
            }  
        }  
        else  
            System.out.println ( " Usage : Java file test <filename (s)  
    }  
}
```

```
public static void getPaths (File f ) throws IOException {  
    System.out.println ( "Name : " + f.  
    getName ( ) );  
    System.out.println ( "Path : " + f.  
    getPath ( ) );  
    System.out.println ( "Parent : " +  
    f.getParent ( ) );  
    public static void getInfo (File f ) throws IOException {  
        if (f.exists ( ) ) {  
            System.out.print ( "File exists " );  
            System.out.println ( f.canRead ( ) ?  
            "and is readable" : "" );  
            System.out.println ( f.canWrite ( )  
            ? "and is writable" : "" );  
            System.out.println ( "File is last  
            modified : " + f.lastModified ( ) );  
            System.out.println ( "File is " +  
            f.length ( ) + "bytes" );  
        }  
        else  
            System.err.println ( " File does not  
            exist." );  
    }  
}
```



Reading a File



Example: class FileInputStream

```
class InputStreamTest
{
    public static void main (String[] args)
    {
        int size;
        // To open a file
        FileInputStream fin;
        fin = new FileInputStream ("data.txt");
        size = fin.available();
        // returns the number of bytes available
        System.out.println ("Total bytes available : " + size);
        System.out.println ("Total bytes read : 0");
        for (int i = 0; i < size; i++)
        {
            System.out.print (b[i]);
        }
    }
}
```

```
System.out.println (" Remaining bytes : " + fin.available() );
System.out.println ("Next ¼ is displayed : Using read( b[ ])");
byte b[] = new byte[size/4];
if (fin.read (b) != b.length )
    System.err.println ("File reading error : ");
else {
    String temp = new String (b, 0, 0, b.length );
    // Convert the bytes into string
    System.out.println (temp) ;
    // display text string.
    System.out.println (" Still available:" + fin.available() );
    System.out.println (" skipping ¼ : Using skip ( )" );
    fin.skip(size/4);
    System.out.println (" File remaining for read ::"
        + fin.available() );
}
fin.close ( ); // Close the input stream
}
```



Writing into a File



Example: Writing bytes into file

```
import java.io.*;

class WriteBytes {
    public static void main(String args[]) {
        cities[]={'D','E','L','H','I','\n','M','A','D','R','A','S','\n','L','O','N','D','O','N','\n'}; //Declare and initialize a byte array byte
        FileOutputStream outfile=null; //create an output file stream
        try {
            outfile = new FileOutputStream("city.txt");
            // Connect the outfile stream to "city.txt"
            outfile.write(cities); //Write data to the stream
            outfile.close();
        }
        catch(IOException ioe) {
            System.out.println(ioe);
            System.exit(-1);
        }
    }
}
```



Reading from a File



Example: Reading bytes from file

```
import java.io.*;
class ReadBytes {
    public static void main (String args[]) {
        FileInputStream infile = null; // Create an input file stream
        int b;
        try {
            infile = new FileInputStream(args[0]);
            // Connect infile stream to the required file
            while((b = infile.read()) != -1) {
                System.out.print((char)b); // Read and display data
            }
            infile.close();
        }
        catch(IOException ioe) {
            System.out.println(ioe);
        }
    }
}
```



Copy a File into Other File
(CharacterStream Class)



Example: Reading/ writing characters

```
//Copying characters from one file into another
import java.io.*;
class CopyCharacters
{
    public static void main (String args[])
    {
        //Declare and create input and output files
        File inFile = new File("input.dat");
        File outFile = new File("output.dat");
        FileReader ins = null; // Creates file stream ins
        FileWriter outs = null;
        // Creates file stream outs
        try {
            ins = new FileReader (inFile) ;
            // Opens inFile
            outs = new FileWriter (outFile) ;
            // Opens outFile
            int ch; // Read and write till the end
```

```
        while ((ch = ins.read()) != -1)
        {
            outs.write(ch) ;
        }
    }
    catch(IOException e) {
        System.out.println(e);
        System.exit(-1);
    }
    finally //Close files
    {
        try {
            ins.close();
            outs.close();
        }
        catch (IOException e) { }
    }
} // main
} // class
```



Copying a File into Other File (ByteStream Class)



Example: Copying bytes from one file to another

```
import java.io.*;
class CopyBytes
{
    public static void main (String args[])
    {
        //Declare input and output file
        streams
        FileInputStream infile = null;
        //Input stream \
        FileOutputStream outfile = null;
        //Output stream
        //Declare a variable to hold a
        byte
        byte byteRead;
```

```
try {
    //Connect infile to in.dat
    infile = new
    FileInputStream("in.dat");
    //Connect outfile to out.dat
    outfile = new
    FileOutputStream("out.dat");
    //Reading bytes from in.dat
    and writing to out.dat
```

```
catch(FileNotFoundException e) {
    System.out.println("File not
    found");
}
catch(IOException e) {
    System.out.println(e.
    getMessage());
}
```

close files

```
catch(FileNotFoundException e) {
    System.out.println("File not
    found");
}
catch(IOException e) {
    System.out.println(e.
    getMessage());
}
finally //Close files
{
    try {
        infile.close();
        outfile.close();
    }
    catch(IOException e){}
}
}
```



Storing Data into a File



Example: Storing and reading data

```
import java.io.*;
class ReadWritePrimitive
{
    public static void main (String args[]) throws IOException
    {
        File primitive = new File("prim.dat");
        FileOutputStream fos = new FileOutputStream(primitive);
        DataOutputStream dos = new DataOutputStream(fos);

        //Write primitive data to the "prim.dat"file
        dos.writeInt(1999);
        dos.writeDouble(375.85);
        dos.writeBoolean(false);
        dos.writeChar('X');
```

```
        dos.close();
        fos.close();
        //Read data from the "prim.dat" file
        FileInputStream fis = new FileInputStream(primitive);
        DataInputStream dis = new DataInputStream(fis);
        System.out.println(dis.readInt());
        System.out.println(dis.readDouble());
        System.out.println(dis.readBoolean());
        System.out.println(dis.readChar());

        dis.close();
        fis.close();
    }
}
```



Example: Storing and reading data in same file

```
import java.io.*;

class ReadWriteIntegers
{
    public static void main (String
    args[])
    {
        DataInput
        DataOutp

        File int
        File("ca
        //Writing integ

        //Create output
```

```
        dos = new DataOutputStream(new FileOutputStream(intFile));
        for(int i=0;i<20;i++)
        {
            dos.writeInt ((int) (Math. random () *100));
            System.out.println(ioe.getMessage());
        }
    }
}
```

```
try {
    dis = new DataInputStream(new
    FileInputStream(intFile)); //Create input stream for intFile file
    for(int i=0;i<20;i++) {
        int n = dis.readInt();
        System.out.print(n + " "); }
    catch(IOException ioe) { }
```

```
catch(IOException ioe)
```

```
try {
    dis = new DataInputStream(new
    FileInputStream(intFile)); //Create input stream for intFile file
    for(int i=0;i<20;i++) {
        int n = dis.readInt();
        System.out.print(n + " "); }
    catch(IOException ioe) {
        System.out.println(ioe.
        getMessage());
    }
    finally {
        try {
            dis.close();
        }
        catch(IOException ioe){ }
    }
}
```



Merging two Files into a File



Example: Concatenation and buffering

```
import java.io.*;
class SequenceBuffer
{
    public static void main (String args[]) throws
    IOException
    {
        //Declare file streams
        FileInputStream file1 = null;
        FileInputStream file2 = null;

        SequenceInputStream file3 = null;
        //Declare file3 to store combined files
        file1 = new FileInputStream("text1.dat");
        //Open the files to be concatenated
        file2 = new FileInputStream("text2.dat");
        //Open the files to be concatenated
        file3 = new SequenceInputStream(file1,file2) ;
        //Concatenate file1 and file2
    }
}
```

```
//Create buffered input and output streams
BufferedInputStream inBuffer = new
BufferedInputStream(file3);
BufferedOutputStream outBuffer = new
BufferedOutputStream(System.out);
//Read and write till the end of buffers
int ch;
while((ch = inBuffer.read()) != -1)
    outBuffer.write((char)ch);
inBuffer.close();
outBuffer.close();
file1.close();
file2.close();
}
```

Thank You

OBJECT ORIENTED PROGRAMMING WITH JAVA

Input-Output Handling in Java - III

Debasis Samanta

Department of Computer Science & Engineering
Indian Institute of Technology Kharagpur



Random Access Files in Java




Use of class `RandomAccessFile`

- As the name implies the class `RandomAccessFile` allows us to handle a file `randomly` in contrast to sequentially in `InputStream` or `OutputStream` classes
- It allows to move file pointer randomly
- Moreover, it allows read or write or read-write simultaneously.



Class: `RandomAccessFile`





Example: RandomAccessFile

```
import java.io.*;
class RandomIO
{
    public static void main (String args[])
    {
        RandomAccessFile file = null;
        try {
            file = new
                RandomAccessFile("rand.dat", "rw");
            // Writing to the file
            file.writeChar('X');
            file.writeInt(555);
            file.writeDouble(3.1412);
            file.seek (0);
            // Go to the beginning
            // Reading from the file
            System.out.println(file.readChar());
```

```
                System.out.println(file.readInt());
                System.out.println(file.readDouble());
                file.seek(2); // Go to the second item
                System.out.println(file.readInt());
                // Go to the end and append false to
                the file
                file.seek(file.length());
                file.writeBoolean(false);
                file.seek (4) ;
                System.out.println(file.readBoolean());
                file.close();
            }
            catch(IOException e)
            {

                System.out.println(e);
            }
        }
    }
}
```



Example: Appending to a RAF

```
import java.io.*;
class RandomAccess
{
    static public void main(String args[])
    {
        RandomAccessFile rFile;
        try
        {
            rFile = new RandomAccessFile("city.txt","rw");

            rFile.seek(rFile.length()); // Go to the end
            rFile.writeByte("MUMBAI\n"); //Append MUMBAI
            rFile.close();
        }
        catch(IOException ioe)
        {
            System.out.println(ioe);
        }
    }
}
```



Interactive Input-Output



Interactive input and output

```
import java.util.*; // For usi
import java.io.*;
class Inventory {
    static DataInputStream din
    static StringTokenizer st;
    public static void main (St
    IOException
    {
        DataOutputStream dos = new
        FileOutputStream("invent.da
        // Reading from console
        System.out.println("Enter c
        st = new StringTokenizer(di
        int code = Integer.parseInt
        System.out.println("Enter r
        st = new StringTokenizer(di
        int items = Integer.parseln
        System.out.println("Enter c
        st = new StringTokenizer(di
        double cost = new    Doubl
```


```
// Writing to the file "invent.dat"
dos.writeInt(code);
dos.writeInt(items);
dos.writeDouble(cost);
dos.close();
// Processing data from the file
DataInputStream dis=new DataInputStream(new
FileInputStream("invent.dat"));
int codeNumber = dis.readInt();
int totalItems = dis.readInt();
double itemCost = dis.readDouble();
double totalCost = total Items * itemCost;
dis.close();
// Writing to console
System.out.println();
System.out.println("Code
System.out.println("Item
System.out.println("Total
System.out.println("Total
}
```

```
// Writing to the file "invent.dat"
dos.writeInt(code);
dos.writeInt(items);
dos.writeDouble(cost);
dos.close();
// Processing data from the file
DataInputStream dis=new DataInputStream(new
FileInputStream("invent.dat"));
int codeNumber = dis.readInt();
int totalItems = dis.readInt();
double itemCost = dis.readDouble();
double totalCost = total Items * itemCost;
dis.close();
// Writing to console
System.out.println();
System.out.println("Code Number : " + codeNumber);
System.out.println("Item Cost : " + itemCost);
System.out.println("Total Items : " + totalItems);
System.out.println("Total Cost : " + totalCost);
}
```



Graphical Input-Output

Graphical input and output



The image shows a Java Swing window titled "Create Student File". The window has a standard title bar with minimize, maximize, and close buttons. The main content area is divided into three rows, each with a label on the left and an input field on the right. The labels are "Roll Number", "Student Name", and "Marks". The input fields are empty text boxes. At the bottom of the window, there are two buttons: "ENTER" and "DONE".

Label	Input Field
Roll Number	
Student Name	
Marks	

ENTER DONE



Graphical input and output

```
import java.io.*;
import java.awt.*;
class StudentFile extends Frame
{
    // Defining window components
    TextField number, name, marks;
    Button enter, done;
    Label numLabel, nameLabel, markLabel;
    DataOutputStream dos;

    // Initialize the Frame
    public StudentFile()
    {
        super("Create Student File");
    }
    // Setup the window
    public void setup()
    {
        resize(400, 200);
        setLayout(new GridLayout(4,2));
        // Create the components of the Frame
```

```
        number = new TextField(25);
        number = new TextField(25);
        numLabel = new Label("Roll Number");
        name = new TextField(25);
        nameLabel = new Label ("Student Name");
        marks = new TextField(25);
        markLabel = new Label("Marks");
        enter = new Button("ENTER");
        done = new Button("DONE");
        // Add the components to the Frame
        add(numLabel);
        add(number);
        add(nameLabel);
        add(name);
        add(markLabel);
        add(marks);
        add(enter);
        add(done);
        // Show the Frame
        show();
```



Graphical input and output

```
// Open the file
try {
    dos new DataOutputStream( new
    FileOutputStream("student.dat"));
}
catch(IOException e) {
    System.err.println(e.toString());
    System.exit(1);
}

// Write to the file
public void addRecord() {
    int num;
    Double d;
    num = (new
    Integer(number.getText())).intValue();
    try {
        dos.writeInt(num);
        dos.writeUTF(name.getText());
        d = new Double(marks.getText());
        dos.writeDouble(d.doubleValue());
    }
```

```
catch(IOException e) { }
    // Clear the text fields
    number.setText(" ");
    name.setText(" ");
    marks.setText(" ");
}
// Adding the record and clearing the
// TextFields
public void cleanup()
{
    if(!number.getText().equals(" ")) {
        addRecord();
    }

    try {
        dos.flush();
        dos.close();
    }
    catch(IOException e) { }
}
```



Graphical input and output

```
// Processing the event
public boolean action(Event
event, Object o)
{
    if(event.target instanceof
        Button)
        if(event.arg.equals("ENTER")) {
            addRecord();
            return true;
        }
    return super.action(event, o);
}
public boolean handleEvent(Event
event)
{
```

```
if(event.target instanceof Button)
    if(event.arg.equals("DONE")) {
        cleanup();
        System.exit(0);
        return true;
    }
    return super.handleEvent(event);
}
// Execute the program
public static void main (String args[])
{
    StudentFile student = new StudentFile();
    student.setup();
}
}
```



Another graphical Input/Output

```
import java.io.*;
import java.awt.*;
class ReadStudentFile extends Frame
{
    // Defining window components
    TextField number, name, marks;
    Button next, done;
    Label numLabel, nameLabel, markLabel;
    DataInputStream dis;
    boolean moreRecords = true;

    // Initialize the Frame
    public ReadStudentFile()
    {
        // Setup the window
        public void setup()
        {
            resize(400,200);
            setLayout(new
            GridLayout(4,2));
            // Create the components of the Frame
```

```
number = new TextField(25);
numLabel = new Label ("Roll Number");
name = new TextField(25);
nameLabel = new Label ("Student Name");
marks = new TextField(25);
markLabel = new Label("Marks");
next new Button("NEXT");
done = new Button("DONE");
// Add the components to the Frame
add(numLabel);
add(number);
add(nameLabel);
add(name);
add(markLabel);
add(marks);
add(next);
add(done);
// Show the Frame
show();
// Open the file
```



Another graphical Input/Output

```
try {
    dis = new DataInputStream(new
        FileInputStream("student.dat"))
    }
    catch(IOException e)
    {
        System.err.println(e.toString());
        System.exit(1);
    }
}

// Read from the file
public void readRecord()
{
    int n;
    String s;
    double d;

    try {
        n = dis.readInt();
```

```
        s = dis.readUTF();
        d = dis.readDouble();
        number.setText(String.valueOf(n));
        name.setText(String.valueOf(s));
        marks.setText(String.valueOf(d));
    }
    catch(IOException ioe) {
        System.out.println("IO ErrorN");
        System.exit(1);
    }
}

// Closing the input file
public void cleanup()
{
    try
    {
        dis.close();
    }
    catch(IOException e) { }
}
```



Another graphical Input/Output

```
// Processing the event
public boolean action(Event event, Object o)
{
    if(event.target instanceof Button)
        if(event.arg.equals("NEXT"))
            readRecord();

    return true;
}

public boolean handleEvent(Event event)
{
    if(event.target instanceof Button)
    if (event.arg.equals ("DONE") || moreRecords ==
        false){
        cleanup();
        System.exit(0);
        return true;
    }
    return super.handleEvent(event);
}
```

```
// Execute the program
public static void main (String
args[])
{
    ReadStudentFile student =
    new ReadStudentFile();
    student.setup();
}
}
```

Question to think...

- How Java helps programmers to develop GUIs?
- How one can develop programs like Google?

Thank You